

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name : Herculiner Truck Bed Liner Black

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Roll-on Truck Bed Liner

1.3. Details of the supplier of the safety data sheet

Old World Industries, LLC 4065 Commercial Ave. Northbrook, IL 60062 - USA T (847) 559-2000 www.oldworldind.com

1.4. Emergency telephone number

Emergency number : (800) 424-9300; (703) 527 3887 (International)

Chemtrec

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

H226 Flam. Liq. 3 Acute Tox. 4 (Dermal) H312 Acute Tox. 4 (Inhalation:dust,mist) H332 Skin Irrit. 2 H315 Eye Irrit. 2A H319 Resp. Sens. 1 H334 Skin Sens. 1 H317 Carc. 2 H351 Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US)







GHS02

GHS07

CHEVO

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H226 - Flammable liquid and vapor

H312+H332 - Harmful in contact with skin or if inhaled

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction H319 - Causes serious eye irritation

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled

H335 - May cause respiratory irritation

Precautionary statements (GHS-US) : P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking

P233 - Keep container tightly closed

P260 - Do not breathe mist, spray, vapors P264 - Wash affected areas thoroughly after handling

P264 - Wash affected areas thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear personal protective equipment as required

P284 - [In case of inadequate ventilation] wear respiratory protection

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

03/20/2015 EN (English) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

lenses, if present and easy to do. Continue rinsing

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention

P337+P313 - If eye irritation persists: Get medical advice/attention

P342+P311 - If experiencing respiratory symptoms: Call a doctor/physician or poison center

P362+P364 - Take off contaminated clothing and wash it before reuse

P370+P378 - In case of fire: Use foam/dry powder/carbon dioxide to extinguish

P403+P235 - Store in a well-ventilated place. Keep cool

P405 - Store locked up

P501 - Dispose of contents/container, in a safe manner, to to appropriate waste disposal

facility, in accordance with local/regional/national/international regulations.

2.3 Other hazards

No additional information available

Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

Substance

Not applicable

3.2. **Mixture**

Name	Product identifier	% by wt	GHS-US classification
xylene, mixture of isomers	(CAS No) 1330-20-7	<= 29.4	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315
polymethylene polyphenyl isocyanate	(CAS No) 9016-87-9	<= 5	Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373

SECTION 4: First aid measures

Description of first aid measures 4.1.

First-aid measures general

: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Symptoms of poisoning may not appear for several hours. supervision of a doctor is necessary during at least 48h after an accident happened.

First-aid measures after inhalation

: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Get immediate medical advice/attention. If not breathing, give artificial respiration.

First-aid measures after skin contact

Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical

First-aid measures after eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes. If eye irritation persists: Get immediate medical advice/attention.

First-aid measures after ingestion

Rinse mouth. Drink plenty of water. Do NOT induce vomiting. Obtain emergency medical attention. A person vomiting while laying on their back should be turned onto their side.

Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation

: May cause allergy or asthma symptoms or breathing difficulties if inhaled. Vapor inhalation and/or skin absorption can cause central nervous system effects, including dizziness, lightheadedness, headache, nausea and loss of coordination. Prolonged exposure to small concentrations may result in pulmonary oedema.

Symptoms/injuries after skin contact

Causes skin irritation. May cause an allergic skin reaction.

Symptoms/injuries after eye contact

Causes serious eye irritation.

Symptoms/injuries after ingestion

Nausea. Gastrointestinal complaints. Dizziness.

Indication of any immediate medical attention and special treatment needed

If swallowed or in case of vomitting, danger of entering the lungs. Severe allergic skin reaction, bronchial spasms and anaphylactic shock are possible. In cases of irritation to the lungs, initial treatement with cortical steroid inhalants. If necessary oxygen respiration treatment. Treat skin and mucous membrane with anithistamine and corticoid preparations. Contains diphenylmethanediisocyanate, isomers and homologues. May produce an allergic reaction

03/20/2015 EN (English) 2/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapor. During a fire, smoke may contain the original material in addition

to combustion products of varying composition which may be toxic and/or irritating. Combustion

products may include and are not limited to: Carbon monoxide. Carbon dioxide.

Explosion hazard : May form flammable/explosive vapor-air mixture.

Reactivity : Cures with exposure to water vapor.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking, Isolate from fire, if possible, without unnecessary risk.

6.1.1. For non-emergency personnel

Protective equipment : Wear suitable respiratory equipment in case of insufficient ventilation.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection. Refer to section 8.2.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Leave the product to solidify. Take up mechanically (sweeping, shovelling) and collect in

suitable container for disposal. Ensure adequate ventilation, especially in confined areas. Do

not flush with water.

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect

spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation

of vapor.

Hygiene measures : Wash affected areas thoroughly after handling. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Direct sunlight,

Heat sources. Do not store near food, foodstuffs, drugs or potable water supplies. Store in a well-ventilated place. Keep container tightly closed. Do not allow water (or moist air) contact

with this material.

Incompatible products : Keep away from strong acids, strong bases and oxidizing agents.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

7.3. Specific end use(s)

No additional information available

03/20/2015 EN (English) 3/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Herculiner Truck Bed Liner Black		
SUPPLIER	TWA (mg/m³)	0.045 mg/m³ Limits not to be exceeded at any time.
SUPPLIER	TWA (ppm)	0.005 ppm Limits not to be exceeded at any time.
SUPPLIER	Remark	Contains Isocyanate (as - NCO) which is an ingredient with limit values that require monitoring at the workplace
xylene, mixture of isomers (1330-20-7)	
USA ACGIH	ACGIH TWA (ppm)	100.00 ppm
USA ACGIH	ACGIH STEL (ppm)	150.00 ppm
USA ACGIH	Remark (ACGIH)	Upper Respiratory Tract & eye irritant; Central Nervous System impairment
USA OSHA	OSHA PEL (TWA) (mg/m³)	435.00 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	100.00 ppm

8.2. Exposure controls

Personal protective equipment : Avoid all unnecessary exposure. Gloves. Safety glasses. High gas/vapor concentration: gas







Hand protection : Wear protective gloves.

Eye protection : Chemical goggles or safety glasses.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : In case of inadequate ventilation wear respiratory protection. Combined gas/dust mask with

filter type A/P2.

Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Pigment.
Color : Black

Odor : Petroleum-like odor
Odor threshold : No data available
Relative evaporation rate (butylacetate=1) : No data available
Freezing point : No data available
Boiling point : 154 °C (309 °F)

Flash point : 27 °C (81 °F) Method Used: TCC

Vapor pressure : 8 - 9 mm Hg (@ 25 °C [77 °F])

Relative vapor density at 20 °C : 3 (@ 68 °F)

Specific Gravity : 1.06 (.865 Xylene Only)

Density : 1.03 g/cm³

Solubility : Water: Forms solid gel
Log Pow : No data available
Log Kow : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available
Explosive properties : No data available

03/20/2015 EN (English) 4/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Oxidizing properties : No data available Explosive limits : 1 - 7 vol %

9.2. Other information

VOC content : 29.40 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Cures with exposure to water vapor.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Keep away from strong acids, strong bases and oxidizing agents. water.

10.6. Hazardous decomposition products

May release flammable gases. Carbon monoxide. Carbon dioxide. Fume. Hydrogen cyanide. (prussic acid). Isocyanates. Nitrogen oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Herculiner Truck Bed Liner Black

Acute toxicity : Dermal: Harmful in contact with skin. Inhalation:dust,mist: Harmful if inhaled.

ATE US (dermal)	1,100 mg/kg bodyweight
ATE US (dust,mist)	2 mg/l/4h
xylene, mixture of isomers (1330-20-7)	
LD50 oral rat	3523 - 8600 mg/kg (3523 mg/kg bodyweight; >4000 mg/kg bodyweight; Rat; Rat; Experimental value; Experimental value)
LD50 dermal rabbit	> 4,200 mg/kg bodyweight (Rabbit; Experimental value, Rabbit; Experimental value)
LC50 inhalation rat (mg/l)	29 mg/l/4h (27.57 mg/l/4h; Rat; Rat; Experimental value; Experimental value,27.57 mg/l/4h; Rat; Rat; Experimental value; Experimental value)
ATE US (oral)	3,523 mg/kg bodyweight
ATE US (dermal)	1,100 mg/kg bodyweight
ATE US (gases)	4,500 ppmv/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust,mist)	2 mg/l/4h

polymethylene polyphenyl isocyanate (9016-87-9)		
LD50 oral rat	> 10,000 mg/kg (Rat; Literature study)	
LD50 dermal rabbit	> 5,000 mg/kg (Rabbit; Literature study)	
ATE US (gases)	4,500 ppmv/4h	
ATE US (vapors)	11 mg/l/4h	
ATE US (dust,mist)	2 mg/l/4h	

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an

allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Suspected of causing cancer.

xylene, mixture of isomers (1330-20-7)	
IARC group	3 - Not classifiable
polymethylene polyphenyl isocyanate (9016-87-9)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
Reproductive toxicity	: Not classified

03/20/2015 EN (English) 5/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

vylono	mivturo	of isomers	(1330-20-7)
xylene.	, illixture	orisomers	(1330-20-7)

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated

Potential adverse human health effects and

exposure)

: Not classified

Aspiration hazard : Not classified

: Based on available data, the classification criteria are not met.

symptoms Symptoms/injuries after inhalation : May cause allergy or asthma symptoms or breathing difficulties if inhaled. Vapor inhalation

> and/or skin absorption can cause central nervous system effects, including dizziness, lightheadedness, headache, nausea and loss of coordination. Prolonged exposure to small

concentrations may result in pulmonary oedema.

Symptoms/injuries after skin contact Causes skin irritation. May cause an allergic skin reaction.

Symptoms/injuries after eye contact Causes serious eye irritation.

Symptoms/injuries after ingestion : Nausea. Gastrointestinal complaints. Dizziness.

SECTION 12: Ecological information

12.1. **Toxicity**

xylene, mixture of isomers (1330-20-7)		
LC50 fish 1	14 mg/l (96 h; Lepomis macrochirus; Lethal)	
EC50 Daphnia 1	150 mg/l (24 h; Daphnia magna)	
LC50 fish 2	4 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)	
EC50 Daphnia 2	7 mg/l (48 h; Daphnia magna)	
Threshold limit algae 1	72 mg/l (336 h; Selenastrum capricornutum; Growth)	
Threshold limit algae 2	10 mg/l (72 h; Skeletonema costatum)	
polymethylene polyphenyl isocyanate (9016-87-9)		
LC50 other aquatic organisms 1	> 1,000 mg/l (96 h)	
Threshold limit other aquatic organisms 1	> 1,000 mg/l (96 h)	

12.2. Persistence and degradability

xylene, mixture of isomers (1330-20-7)		
Persistence and degradability Readily biodegradable in water. Biodegradable in the soil. Photolysis in the air.		
polymethylene polyphenyl isocyanate (9016-87-9)		
Persistence and degradability	Not readily biodegradable in water. Hydrolysis in water. No (test)data on mobility of the substance available.	

12.3. **Bioaccumulative potential**

xylene, mixture of isomers (1330-20-7)		
BCF fish 1	15 8 weeks; Salmo gairdneri (Oncorhynchus mykiss)	
BCF fish 2	7 - 26 (8 weeks; Oncorhynchus mykiss)	
Log Pow	3.2 (20 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).	
polymethylene polyphenyl isocyanate (9016-87-9)		
BCF fish 1	1 (Pisces)	
Bioaccumulative potential	Not bioaccumulative.	

12.4. **Mobility in soil**

xylene, mixture of isomers (1330-20-7)	
Ecology - soil	May be harmful to plant growth, blooming and fruit formation.

Other adverse effects

Effect on ozone layer : No additional information available

Effect on global warming : No known ecological damage caused by this product.

Effect on global warming : No additional information available

Other information : Avoid release to the environment.

03/20/2015 EN (English) 6/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: Disposal considerations

Waste treatment methods

Waste disposal recommendations : Dispose of contents/container, in a safe manner, to an approved waste disposal site in

accordance with local/regional/national regulations.

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials Avoid release to the environment.

SECTION 14: Transport information

In accordance with DOT

Not a dangerous good in sense of transport regulations

Other information

: DOT Consumer Commodity Exemption (Part 172,150) Outer Packaging: "Consumer Commodity - ORM-D" and ISO orientation arrows. Pallets: If "Consumer Commodity" on outer packaging is visibile lableling not required. Otherwise label as "Consumer Commodity."

Container/Trailer: None required.

ADR

No additional information available

Transport by sea

Limited quantities (IMDG) : IMDG Exemption for Limited Quantities (IMDG 18.3, 3.26)

Outer Packaging: (No requirements)

Pallets: Dangerous Goods in Limited Quantities (Class 3 Flammable)

Container: "Limited Quantities"

Air transport

Instruction "passenger" - Limited quantities

(ICAO)

: IATA Limited Quantities Exemption (Part 2.8) For Shipping of product 10 Liters and Under in one Package: Packing Instruction Y309 (No UN Packaging Required). Labels Required: Paint, Flammable Liquid, 3, ISO orientation arrows, shipper and consignee information, and the statement "LTD. QTY". For Shipping of product over 10 Liters in one Package:Packing Instruction 309 or 310 dependent aircraft type (UN Packaging Required). Labels Required: Paint, Flammable Liquid, 3, ISO orientation arrows (cargo only aircraft label if applicable),

shipper and consignee information.

SECTION 15: Regulatory information

15.1. US Federal regulations

Herculiner Truck Bed Liner Black	
EPA TSCA Regulatory Flag	Toxic Substances Control Act (TSCA): The intentional ingredients of this product are listed 9016-87-9 diphenylmethanediisocyanate, isomers and homologues CBD
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard Fire hazard
SARA Section 313 - Emission Reporting	5 % 9016-87-9 diphenylmethanediisocyanate, isomers and homologues

15.2. International regulations

CANADA

Herculiner Truck Bed Liner Black	
WHMIS Classification	Class B Division 3 - Combustible Liquid

WHMIS Classification



Class B Division 3 Combustible Liquid

EU-Regulations

No additional information available

03/20/2015 EN (English) 7/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

15.2.2. National regulations

xylene, mixture of isomers (1330-20-7)

Listed on RCRA Hazardous Substances Xylenes (1330-20-7) RCRA Code: U239

Listed on CERCLA Hazardous Substances List (RQ 1000 lb)

Listed on the SC Toxic Air Pollutants List

Listed on Title V

15.3. US State regulations

xylene, mixture of isomers (1330-20-7)

- U.S. Pennsylvania RTK (Right to Know) List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Massachusetts Right To Know List

SECTION 16: Other information

Full text of H-phrases:

kt of Fi-prilases.	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 3	Flammable liquids, Category 3
Resp. Sens. 1	Sensitisation — Respiratory, category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Sensitisation — Skin, category 1
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H226	Flammable liquid and vapor
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335	May cause respiratory irritation
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated
	exposure

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt

medical attention is given.

: 3 - Liquids and solids that can be ignited under almost all

ambient conditions.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.

2 0

HMIS III Rating

NFPA fire hazard

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 3 Serious Hazard
Physical : 0 Minimal Hazard

03/20/2015 EN (English) 8/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SDS GHS US (GHS HazCom 2012) OWI

Old World Industries, LLC makes no warranty, representation or guarantee as to the accuracy, sufficiency or completeness of the material set forth herein. It is the user's responsibility to determine the safety, toxicity and suitability of his own use, handling and disposal of this product. Since actual use by others is beyond our control, no warranty, expressed or implied, is made by Old World Industries, LLC as to the effects of such use, the results to be obtained or the safety and toxicity of this product, nor does Old World Industries, LLC assume liability arising out of the use by others of this product referred to herein. The data in this SDS relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

03/20/2015 EN (English) 9/9